

DELTA COLUMN

The column protector Delta consists of four corner posts of the Delta safety barrier, which are connected with the associated spar sets to a square. The height of the column protection amounts to 1,200 mm, the spar sets can be ordered in lengths of 705 mm and 1,510 mm. Of course, the column protection Delta also offers the possibility of ordering individual lengths between 350 mm and 1,510 mm.

Width: 705 mm / 1510 mm / individual

Length: 705 mm / 1510 mm / Customized Lengths

Height: 1200 mm



FACTS

| ART. NO | COMPONENTS |
|----------|--|
| 12000031 | Delta Colomn Protector L=600mm |
| 12000032 | Delta Colomn Protector L=1305mm |
| 12000033 | Delta Colomn Protector Individual length |

Technical Information

- Tested to withstand force of (Joule) 2.500J
- Vehicle weight equivalent (kg) 2.000 kg
- Vehicle equivalent speed (km/h) 5,7 km/h
- Equivalent angle of impact 90°
- Deflection zone 250 mm

Material Properties

- Chemical Resistance high ISO/TR 10358
- Temperature Range -10° up to + 50°
- Recyclability 100%
- Material: Polyethylene

Other

• Color: Yellow (like RAL 1018 traffic yellow) / black



Indoor use: YesOutdoor use: Yes

• Boreholes: 4

• Fixing: The fixing material is included.

• Fixing dimensions: M10X70 mm



COMBINE WITH



BRAVO



DELTA 3 BEAM







DELTA 4 BEAM