

NOVEMBER

In daily use the d-flexx Dock Gate convinces with its easy handling. It can be opened and closed by one person - simple and uncomplicated. The built-in safety spring also prevents the cross tube from lowering or falling abruptly, thus ensuring safe use. In combination with our other d-flexx products a complete barrier is created. Like the other d-flexx products, November is made of polyethylene to absorb the impact force and then return to its original shape. The Dock Gate is pre-assembled and the mounting hardware is included in the delivery. Dock Gate November are available in two standard opening widths of 2300 and 2600 mm, individual cutting from 2300 to 3300 mm possible.

Width: 585 mm

Length: 2750 mm / 3050 mm

Height: 516 mm



FACTS

ART. NO	COMPONENTS
12000073	November gate 2300mm Ø200mm
12000074	November gate 2600mm Ø200mm
12000075	November Ind. Length Ø200mm, 2750-3750mm

Technical Information

- Tested to withstand force of (Joule) 5.600J
- Vehicle weight equivalent (kg) 3.000 kg
- Vehicle equivalent speed (km/h) 7,0 km/h
- Equivalent angle of impact 90°
- Deflection zone 250 mm

Material Properties

- Chemical Resistance high - ISO/TR 10358
- Temperature Range -10° up to + 50°
- Recyclability 100%



NOVEMBER

MACHINE GUARD
WAREHOUSE PARTITIONING
AUTOMATED WAREHOUSE

- Material: Polyethylene

Other

- Color: Yellow (like RAL 1018 traffic yellow) / black
- Indoor use: Yes
- Outdoor use: Yes
- Boreholes: 16
- Fixing: The fixing material is included.
- Fixing dimensions: M12X80 mm

COMBINE WITH




BRAVO



CHARLIE



ECHO



MIKE

IMAGES

